

# RoomSensor Pro Datasheet

The Yealink RoomSensor Pro is a multi-functional sensor designed for conference rooms. Built on Yealink's AI algorithm, the product accurately identifies human characteristics and enables precise people counting. It includes various environmental detection functions such as temperature, humidity, and illumination. By establishing a connection and communication with Yealink gateway devices via Bluetooth, it supports active data reporting, enabling intelligent strategies and integration for conference room automation. Functions include automatic reservation, automatic release, and IoT device coordination. The sensor has a wide detection range and can be customized to meet specific detection requirements. The drawing process for custom detection areas is simple and easy to understand, ensuring high detection accuracy and avoiding false alarms or missed detections. The detachable design of the base and body facilitates easy deployment, installation, and maintenance. The all-in-one Yealink RoomSensor Pro enhances conference room monitoring and management, promoting comfortable environments and improving productivity.

## Key features and benefits

### Key features and benefits



Wide detection range

Covers larger areas, reducing the number of deployed sensors and lowering enterprise costs.



Customizable detection area

Supports the drawing of custom detection areas to adapt to different environmental and specific local detection requirements.



Flexible deployment

Supports two fixing methods, using 3M adhesive or drilling, and features a detachable design for easy disassembly and simple maintenance.



Accurate people counting

Utilizes Yealink's AI learning algorithm to achieve high accuracy and prevent false or missed reports.



Supports temperature, humidity, and illumination in meeting rooms, enabling data reporting and integration strategies.




Cloud device management

Allows remote monitoring, management, and diagnostics of devices through YMCS.



Bluetooth protocol communication

Adopts Bluetooth 5.2 protocol for stable connectivity with Yealink gateway devices.



IoT integration

Enables intelligent strategies, including automatic reservation, automatic release, and coordination with IoT devices.

## Specifications

Specification	Description
---------------	-------------

Basic	<ul style="list-style-type: none"> <li>· Detection:</li> <li>- People Counting</li> <li>- Temperature</li> <li>- Humidity</li> <li>- Illuminance</li> </ul>
Sensor	<ul style="list-style-type: none"> <li>· People Counting:</li> <li>- Detection range: Radius 4m circular area (when the installation height is 3m)</li> <li>- Detection distance: <math>\leq 5m</math></li> <li>· Temperature:</li> <li>- Range: <math>0^{\circ}C \sim 40^{\circ}C</math></li> <li>- Resolution: <math>0.1^{\circ}C</math></li> <li>- Accuracy: <math>-2 \sim +3^{\circ}C</math></li> <li>· Humidity:</li> <li>- Range: <math>10 \sim 95\% RH</math></li> <li>- Resolution: <math>0.5\% RH</math></li> <li>- Accuracy: <math>\pm 10\%</math>;</li> <li>· Illuminance:</li> <li>- Range:</li> <li>- First Gear : <math>0 \sim 300lux</math></li> <li>- Second Gear : <math>301 \sim 800lux</math></li> <li>- Third Gear : <math>801 \sim 3000lux</math></li> <li>- Fourth Gear : <math>3001 \sim 20000lux</math></li> <li>- Fifth Gear : <math>20000lux</math> and above</li> <li>- Accuracy: <math>\pm 10\%</math></li> </ul>
Connectivity	<ul style="list-style-type: none"> <li>· Power Supply :</li> <li>- PoE (IEEE 802.3at)</li> <li>- DC 5V /1.2 A</li> <li>· Ethernet: 1 x Ethernet port (10/100Mbps)</li> <li>· Bluetooth: 5.2</li> <li>· USB: 1 x USB-A · LED:</li> <li>- 1×USB LED</li> <li>- 1×System LED</li> <li>· Button: 1 x Reset</li> </ul>
Installation	<ul style="list-style-type: none"> <li>· Method: Ceiling installation</li> <li>· Height: <math>\leq 3m</math> ( The recommended deployment height for the device is between 2.7 meters and 3 meters. )</li> </ul>
Environmental	<ul style="list-style-type: none"> <li>· Operating Temperature: <math>0 \sim 40^{\circ}C</math></li> <li>· Operating Humidity: <math>10 \sim 95\%</math> , non-condensing</li> </ul>
Dimension	<ul style="list-style-type: none"> <li>· weight(g/lb): 187.5/0.41</li> <li>· size(mm/in) : <math>98 \times 98 \times 30.5</math> ( <math>3.86'' \times 3.86'' \times 1.20''</math> )</li> </ul>